

Q1.(2018)

a)

- part fill a measuring cylinder with water
  - measure initial volume
  - place object in water
  - measure final volume
  - volume of object = final volume – initial volume
- 
- fill a displacement / eureka can with water
  - water level with spout
  - place object in water
  - collect displaced water
  - measuring cylinder used to determine volume of displaced water

b)

$$\text{density} = \frac{48.6}{18.0}$$

$$\text{density} = 2.70 \text{ (g/cm}^3\text{)}$$

c)

**limestone**

d)

eye position when using  
measuring cylinder

**or**

water level in can (at start) not  
at level of spout

**or**

not all water displaced by stone  
is collected in container

e)

volume would be lower / higher

Q2.(2020)

a)

$$\text{density} = \frac{\text{mass}}{\text{volume}}$$

**or**

$$\rho = \frac{m}{V}$$

b)

$$998 = \frac{m}{6\,500\,000}$$

$$m = 998 \times 6\,500\,000$$

$$m = 6\,487\,000\,000$$

$$m = 6.487 \times 10^9 \text{ (kg)}$$

c)

$$\text{energy transferred} = \text{power} \times \text{time}$$

**or**

$$E = Pt$$

d)

$$t = 18\,000 \text{ (s)}$$

**or**

$$t = 5 \times 60 \times 60$$

$$E = 1.5 \times 10^9 \times 18\,000$$

$$E = 2.7 \times 10^{13} \text{ (J)}$$

Q3.(2021)

a)

- use a eureka/displacement can
- fill the eureka/displacement can with water
- fill the eureka/displacement can up to the spout
- place lime in eureka/displacement can
- collect water that overflows
- use a measuring cylinder to measure volume of water

**OR**

- use a measuring cylinder
- part fill the measuring cylinder with water
- measure the initial volume of water
- place lime in measuring cylinder
- record new volume of water
- volume of lime = new volume – initial volume

b)

$$\text{mean} = \frac{(2.1+2.1+2.4)}{3}$$

$$\text{mean} = 2.2 \text{ (cm}^3\text{)}$$

c)

allows anomalous results to be identified and ignored

reduces the effect of random errors when using the equipment

d)

$$\text{density} = \frac{84}{120}$$

$$\text{density} = 0.70 \text{ (g/cm}^3\text{)}$$

Q4.(2022)

a)

- measure mass using a balance / scales
- part fill a measuring cylinder with water and measure initial volume
- place rock in water and measure final volume
- volume of rock = final volume – initial volume
- fill a displacement / eureka can with water level with spout
- place rock in water and collect displaced water
- measuring cylinder used to determine volume of displaced water
- volume of rock = volume of displaced water
- use mass and volume to calculate density
- use of:  $\text{density} = \frac{\text{mass}}{\text{volume}}$

b)

maximum density =  $2.65 \text{ (g/cm}^3\text{)}$

minimum density =  $2.45 \text{ (g/cm}^3\text{)}$

c)

chalk or flint

d)

a mean can be calculated

which reduces the effect of  
random errors

Q5.(2024)

a)

$0.0 \text{ to } 10.0 \text{ cm}^3$

b)

the measured volume would be larger

c)

$$0.4 \text{ (cm}^3\text{)}$$

d)

the results are repeatable

e)

subtract 0.02 from the measurement

f)

$$\text{density} = \frac{\text{mass}}{\text{volume}}$$

**or**

$$\rho = \frac{m}{V}$$

g)

$$22 = \frac{m}{0.3}$$

$$m = 22 \times 0.3$$

$$m = 6.6 \text{ (g)}$$